## TEXAS DEPARTMENT OF HEALTH - BUREAU OF RADIATION CONTROL

## ADDITIONAL INFORMATION FOR REGISTRATION OF ACCELERATOR (S)

A Certificate of Registration authorizing operation of an accelerator must be received by your facility **prior to** operation. This includes the initial beam on and commissioning of the accelerator.

Completion of the attached form will assist the Bureau of Radiation Control in evaluating your request for registration of your accelerator. (See 25 Texas Administrative Code(TAC) §289.226 and §289.229) In addition to this form, the following must be submitted:

- Diagram of floor plan of the accelerator vault and surrounding areas
- Shielding calculations
- Operating and safety procedures

For a medical registration you must also submit physician(s) qualifications (training and experience)

In order to correctly complete the shielding calculation form, note the following:

**Workload** - The degree of use of the x-ray unit stated in terms of the weekly exposure of the useful beam at one meter from the source. (Rm<sup>2</sup>)

**Barrier Name** - This should be the name given to the individual barrier. (example: Barrier 1, Barrier A, etc.). Indicate barrier name on copy of room design submitted. Include information for the ceiling and floor as applicable.

**P/S** - Is the barrier a primary (P) or a secondary (S) barrier?

Primary (P) - Is a radiation protective barrier that may be struck by the main or useful beam of radiation.

Secondary (S) - Is a radiation protective barrier, which may *not* be struck by the useful beam of radiation, but only by leakage and/or scattered radiation.

U/C - Is the area uncontrolled (U) or controlled (C)?

Controlled (C) - Is an area, which requires control of access, occupancy, and working conditions for radiation protection purposes.

Uncontrolled (U) - Is any area which does **not** meet the requirements of a controlled area.

- U Use Factor The expected fraction of the workload during which the appropriate beam of radiation may strike the barrier in question. NOTE: For a secondary barrier (U) is always 1.
- **T** Occupancy Factor The maximum fraction of time during which the area shielded by the barrier in question may be occupied by a person.

**Distance - Primary -** The distance in meters from the isocenter to the point of incidence on the primary barrier.

**Distance - Secondary -** The distance in meters from the isocenter to the point of incidence on the secondary barrier.

Include information for the ceiling and floor.

## ACCELERATOR SHIELDING CALCULATIONS

Facility Name:				
Room Name:				
Workload:	Rm <sup>2</sup> /week	<u> </u>		
Voltage:	MV			
Registration Number:				
LABEL BARRIER	NAME ON COPY OF ROOM DE	ESIGN	SUBMITTED	
Barrier Name:	circle - Primary circle - Controlled			
Use Factor Occupancy Factor Distance to Primary Barrier Distance to Secondary Barrier Thickness of Barrier cm Type of Barrier Material:	meters meters	,	Chechuronea	
circle - Pb concrete iron	*other (specify) include tenth value layer thickness			
Barrier Name: Use Factor	circle - Primary circle - Controlled	/	Secondary Uncontrolled	
Occupancy Factor Distance to Primary Barrier Distance to Secondary Barrier cm Type of Barrier Material:	meters			
	*other (specify)include tenth value layer thickness			
Barrier Name:	circle - Primary circle - Controlled	/	Secondary Uncontrolled	
Use Factor Occupancy Factor Distance to Primary Barrier Distance to Secondary Barrier Thickness of Barrier cm Type of Barrier Material:	meters meters			
	*other(specify) include tenth value layer thickness			

<sup>\*</sup>If materials other than those listed are recommended, the tenth-value thickness at the appropriate energy must be entered.

Barrier Name:	circle - Primary /	Secondary
II. P. A	circle - Controlled /	Uncontrolled
Use Factor		
Occupancy Factor	,	
Distance to Primary Barrier		
Distance to Secondary Barrier		
Thickness of Barriercm		
Type of Barrier Material:		
circle - Pb concrete iron	*other(specify) include tenth value layer thickness	
Barrier Name:	circle - Primary / circle - Controlled /	Secondary Uncontrolled
Use Factor		
Occupancy Factor		
Distance to Primary Barrier	meters	
Distance to Secondary Barrier	meters	
Thickness of Barriercm		
Type of Barrier Material:		
circle - Pb concrete iron	*other(specify) include tenth value layer thickness	
Barrier Name: Ceiling	circle - Primary circle - Controlled	/ Secondary / Uncontrolled
Use Factor		
Occupancy Factor		
Distance to Primary Barrier		
Distance to Secondary Barrier	meters	
Thickness of Barriercm		
Type of Barrier Material:		
circle - Pb concrete iron	*other(specify)	
chere is concrete non	include tenth value layer thickness	
	merade tentii varde layer tinekness	
Barrier Name: Floor (if applicable)	circle - Primary / circle - Controlled /	Secondary Uncontrolled
Use Factor		
Occupancy Factor		
Distance to Primary Barrier		
Distance to Secondary Barrier	meters	
Thickness of Barriercm		
Type of Barrier Material:		
1 10	* (1 ( 'C)	
circle - Pb concrete iron	*other(specify)	
	include tenth value layer thickness	